

UCP-108


8 ZONE CONVENTIONAL FIRE ALARM PANEL

The UCP-108 supports 8 zones and can accommodate up to 32 conventional detectors and manual call points, with a maximum of eight zones. Coming with a robust metal body design, simple installation, and great performance. The panel complies with all European Standards' technical requirements.



FEATURES & BENEFITS

- ✓ Each zone can have up to 32 conventional detectors
- ✓ Indicator Panel that is simple to use and manage
- ✓ Each zone has its own fire and error LEDs
- ✓ Extending battery life with smart battery charging advanced feature.
- ✓ Intelligent start feature that prevents starting directly from battery
- ✓ Individually disabling for each zone
- ✓ Monitoring Siren Outputs and Zone Inputs for any faulty connections with EOL Resistances
- ✓ Two 500mA Siren Outputs for a total of 50 sounder connections (if ULTRA UCSF-116 sounders are used)
- ✓ 24VDC 500mA external supply output with automatic fuse (AUX)
- ✓ 1x Fire Relay (NC/NO) (Button alarm, detector alarm, etc.)
- ✓ 1x Error Relay (NC/NO) (Energy, Zone, and Battery Outage...etc)
- ✓ Unauthorized access is prevented by using a key lock
- ✓ SMPS (Switch Mode Power Supply): (27.6VDC SMPS 1.5Ah automatic fuse)



For more information

+44 (0) 1302 244 903 London, UK


Learn more about ULTRA FIRE PROTECTION SYSTEM and other products available by visiting

www.ultrafire-uk.com

UCP-108

8 ZONE CONVENTIONAL FIRE ALARM PANEL

TECHNICAL SPECIFICATIONS	UCP-108
Standard	EN2-54 / EN4-54
Number of Zones	8
Maximum Numbers of Detectors	32
EOL	4K7 ohm, 4/1,5%W
Operating Voltage & Frequency	110 / 230 VAC (60 / 50 , (15%- / 10%+ Hz (5%±)
Fuse Current	2A
Backup Battery	2X 12V, 7Ah
Imin , ImaxA , ImaxB	75mA , 500 mA , 1,5 A
Number of Monitored Sounder Outputs	2X 500mA
Sounder EOL	4K7 OHM, 4/1,5%W
General Error Relay	1 X NC/NO Dry Contact, 30V, 2A
Fire Relay	1 X NC/NO Dry Contact, 30V, 2A
AUX Output	1X 24VDC 500mA
Dimensions (mm)	340 x 300 x 100 mm
Body material	Metal
Weight	4,4kg (Without Battery)
Operating Temperature	°10-C ~ °55C
Humidity	%95 RH
Protection Class	IP30



For more information

+44 (0) 1302 244 903 London, UK

Learn more about ULTRA FIRE PROTECTION SYSTEM and other products available by visiting www.ultrafire-uk.com