

## UCSF-116 CONVENTIONAL FIRE ALARM SOUNDER WITH FLASHER




Internal fire alarm sounder and flasher ULTRA UCSF-116 feature an attractive design and minimal power consumption, in addition to being compatible with any brand of fire detection systems.



### FEATURES & BENEFITS

- ✓ EN 54-3 and EN 54-23 Certified
- ✓ Suitable for flush and surface mounting
- ✓ Loudness of 100 decibels
- ✓ IP21C protection level
- ✓ Non-flammable UL94 polycarbonate plastic frame in red.

TECHNICAL SPECIFICATIONS	UCSF-116
Standard	EN-54/3 EN-54/23
Sound Level	100dB±2 dB, (24VDC at 1 mt)
Coverage	W-2,4-4
Flasher	1 sec ON / 1 sec OFF
LED	RED
LED Specifications	Wide angle 7x Bright LED
Sounder	Piezzo Element with leak-proof sealant
Operating Voltage	24-28 VDC
Alarm Current Consumption	19mA.
Dimensions (mm)	Ø110, h:55 mm
Body Material	ABS Plastic
Operating Temperature	-20°C - 55°C
Humidity	95% RH
Protection Class	IP21C



### For more information

+44 (0) 1302 244 903 London, UK

Learn more about ULTRA FIRE PROTECTION SYSTEM and other products available by visiting [www.ultrafire-uk.com](http://www.ultrafire-uk.com)